



# Silglaze N10

## One Part Neutral Cure Silicone Sealant

### Product Description

Silglaze N10 is a one component silicone sealant which cures to a high modulus silicone rubber on exposure to atmospheric moisture at room temperature. This product is a neutral cure sealant. In addition to the unique features of silicone rubber such as superior high and low temperatures resistance, water resistance, and outstanding weatherability, Silglaze N10 also provides excellent adhesion to glass, metal and numerous construction materials.

### Key Features and Typical Benefits

- One component, ready-to-use sealant
- Neutral cure
- Fast skinning and curing
- Maintains good flexibility
- Excellent adhesion to glass, aluminum and most building substrates
- Available in 7 standard colors

### Packaging

310ml cartridge available in cases of 50 (5 boxes of 10 cartridges)

### Potential Applications

- Sealing for glass-to-glass and glass-to-metal sash
- Sealant for housing windows, freight container, metal cladding, ducting and interior sealing in building and housing
- Sealing for general glazing and showroom glazing and general weatherproofing applications

Note; Silglaze N10 is not suitable for Structural Glazing use.

### Colors

- Available in 7 colors (Color Suffix): Clear (C); White (W); Gray (G); Light gray (G2); Black (B); Dark brown (A5), Aluminum gray (S)

### Typical Physical Properties

#### Typical Properties – Uncured

Property	Value
Consistency	Paste
Slump ( w=20mm ) *1	0mm
Tack-free time (23°C) * 1	10min
Curing time (t=5mm, 20°C/55%RH)	2days

#### Typical Properties – Cured

Property	Value
Appearance	Elastic rubber
Hardness (Type A) *2	26
Tensile strength *2	1.7MPa
Elongation *2	350%
Peel strength *3	2.8kN/m
Joint movement capability *4	25%
UV resistance *3	Excellent

Test Method: \*1; JIA A 1439 \*2; JIS K 6249 \*3; ASTM C 794 \*4; ASTM C 719

Typical property data values should not be used as specifications. Assistance and specifications are available by contacting GE Toshiba Silicones Commercial Office.

## Installation

### Surface Preparation

Substrate surface should be thoroughly cleaned with a suitable solvent such as alcohol, xylene, or methyl ethyl ketone (MEK). Do not use soap, detergent or water. Wipe the surface dry. Sealant will not properly adhere to a wet substrate. For polycarbonate and acrylic resin, n-hexane should be used in order to prevent solvent-cracking.

### Masking

To obtain a neat sealant line, use masking tape to cover areas adjacent to any joints before priming.

### Primers

It is recommended that preliminary adhesion test be carried out on the substrate to ascertain the adhesion of Silglaze N10. If necessary, primer may be used to improve the bonding performance. Primer can be selected in the selection guide as below. Coated primer should be dried thoroughly before sealant application.

- Mortar, stone and masonry ;TOSPRIME C
- Glass, ceramic, Metal ;TOSPRIME D
- Painted metal, Plastics and rubber ;TOSPRIME E

Caution: Primers contain solvents, which are highly flammable and toxic. Observe all cautions. Storage and use must be done in a well-ventilated area away from any source of ignition such as heat, sparks and flame.

### Back-up Material

Do not apply sealant in direct contact with organic rubber such as chloroprene, EPT, etc. These rubbers may stain the silicone sealant.

### Applying and tooling sealant

Cut nozzle to desired bead size, break the membrane film completely and extrude sealant in the joint. Tool immediately, within 5 minutes, with a spatula to spread the sealant against the back-up material and joint surface. Remove masking tape immediately after tooling. Sealant will begin to skin on the exposed surface in about 15 minutes and cure will progress inward.

## Applicable Standards

SilGlaze N10 Silicone Sealant meets or exceeds the requirements of the following specifications:

- JIA A5758 code regulation (F, G-30SLM)
- ASTM C920, Type S, Grade NS, Class 25
- BS5889, Type B

## Technical Services

For additional technical resources, please contact your local customer service center. (See Customer Service Centers section herein for contact information.) Any technical advice furnished by MPM or any representative of MPM concerning any use or application of any MPM product is believed to be reliable, but MPM makes no warranty, expressed or implied, of suitability for use in any application for which such advice is furnished.

## Limitations

Customers must evaluate MPM products and make their own determination as to the fitness of use in their particular applications.

## STORAGE

- Store in a cool, dry, dark place.
- Keep out of reach of children.
- Shelf life is 18 months from date of manufacture when stored in original, unopened containers below 25°C in a dry place.

## Patent Status

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute the permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

## Product Safety, Handling, and Storage

Customers considering the use of this product should review the latest Safety Data Sheet and label for product safety information, handling instructions, personal protective equipment if necessary, and any special storage conditions required. Material Safety Data Sheets are upon request, from any MPM representative. Use of other materials in conjunction with MPM products (for example, primers) may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

## Customer Service Centers

<b>Americas</b>	+1 800 295 2392 +1 704 805 6946 Email: <a href="mailto:commercial.services@momentive.com">commercial.services@momentive.com</a>
<b>Europe, Middle East, Africa, and India</b>	+00 800 4321 1000 +40 212 044229 Email: <a href="mailto:4information.eu@momentive.com">4information.eu@momentive.com</a>
<b>Asia Pacific</b>	<b>Japan</b> +0120 975 400 +81 276 20 6182  <b>China</b> +800 820 0202 +86 21 3860 4892  <b>All APAC</b> +60 3 9206 1543 Email: <a href="mailto:4information.ap@momentive.com">4information.ap@momentive.com</a>
<b><a href="http://www.siliconeforbuilding.com">www.siliconeforbuilding.com</a></b>	

THE MATERIALS, PRODUCTS, AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS, OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS, OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service, or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service, or design in the infringement of any patent or other intellectual property right.

GE is a registered trademark of General Electric Company and is used under license by Momentive Performance Materials Inc.

Copyright 2018 Momentive Performance Materials Inc. All rights reserved.

