

KM T-F3601FR

Flame Retardant Aluminum Foil Tape

Features:

- *Very Flexible 36µm Aluminum Tape*
- *Coated with Long Lasting Ultraviolet Resistant Acrylic Adhesive on one-side & lined with a release paper.*
- *Pressure Sensitive Self Adhesion*
- *High Resistance to Abrasion & Punctures*
- *Aging Resistance*
- *Vapor Tight*
- *Flame Retardant*



Applications:

- *Joint Sealing of Foil- Laminated fiberglass insulation*
- *Used in RHVAC industry for sealing joints, seams against moisture and vapor penetration on foil jacketing insulation*

Specifications (Based on ASTM D-1000):

<i>Backing</i>	: 36 µm Aluminum Foil
<i>Adhesive</i>	: Acrylic
<i>Thickness</i>	: 0.075 mm
<i>Adhesion to steel @23°C</i>	: >6N per 25mm
<i>Tensile Strength</i>	: 55N per 25mm
<i>Elongation at Break</i>	: 5%
<i>Service Temperature</i>	: -40°C to 90°C
<i>Length</i>	: 45 Metre
<i>Width available</i>	: 50mm, 63mm (Other sizes available on request)

Distributor:

TWO NINE SIX O Trading Pte Ltd

No. 18, Fan Yoong Road,

Singapore 629 795

Tel: 6267 1300 Fax: 6264 2960