

# MC-202

## X' MASTIC NON-SKINNING COLDROOM SEALANT

**DESCRIPTION:**

**x'traseal®** X' MASTIC is a one component, non-drying polybutene rubber based mastic that does not harden but rather remains permanently soft and paste-like. Excellent resistance to water vapour transmission.

**FEATURES:**

- ♦ Permanently non-skinning.
- ♦ Low shrinkage.
- ♦ Moisture resistance.
- ♦ Excellent adhesion.

**USES:**

It's suitable for all kinds of plastics, metals, glass, masonry and timber.

It also can be used in the installation of cold storage, clean room and prefabricated construction.

**WE RECOMMEND PRELIMINARY COMPATIBILITY TESTS PRIOR TO APPLICATION TO ACHIEVE DESIRABLE RESULTS**

**NOT RECOMMENDED FOR:**

It should not be applied in exposed joints where dirt pick-up and hand contact.

Not for: used in areas subject to considerable dynamic stress.

Not for: mobile homes, truck bodies.

**COLOUR:**

White, almond. Other colours are available upon request.

**APPLICATION:**

- ♦ Surface must be clean and dry.
- ♦ Cut nozzle to desired size.
- ♦ Insert cartridge into caulking gun.
- ♦ Push sealant ahead for uniform bead.
- ♦ Clean off excess sealant with kerosene or mineral spirits.

**SPECIFICATION :**

Form	Non-sagging paste.
Colour	White
Specific gravity	1.55 ± 0.05
Slump	2.5 mm maximum
Shrinkage	5 % maximum
Application temp	5 ° C TO 40° C
Service temp.	- 40° C TO 80° C
Shelf life	12 months

**CAUTION:**

Read and understand material safety data sheet of this product before handling or using.

*This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.*

